

GETCERTKEY



GETCERTKEY

100% guarantee you pass IT cert exam!

Instant Update

We are checking our exam questions all the time.



Security & Privacy



24/7 customer support

Free Demo Download

Try before you buy, Download a free sample of any of our exam questions and answers.



One Year Free Update

Free update is available within One Year after your purchase.



<http://www.getcertkey.com>

No help, Full refund!

Exam : 74-134

Title : Pre-Installing MS Products using the OEM Pre-Install Kit

Vendors : Microsoft

Version : DEMO

NO.1 You are a system builder. Your network uses a Microsoft Windows Server? 2003 that is running

the Dynamic Host Configuration Protocol (DHCP) service and is set up as a technician computer.

You installed OPKTools from Microsoft Windows? XP Service Pack 2. You run Setup Manager and

create a configuration set to install a Microsoft Windows operating system. You edit the winbom.ini file in the configuration set and copy the winbom.ini file to a floppy disk. You boot the

master computer by using your Microsoft Windows Preinstallation Environment CD, and you insert the floppy disk with the winbom.ini file. You get the following error message: Cannot Authenticate to the Server. What should you do? (Each correct answer presents a complete solution. Choose two.)

A. Verify that the passwords used for connecting are the same in the configuration set and on the floppy disk.

B. Verify that the Gateway= parameter is included in the winbom.ini answer file.

C. Verify that the StartNet=yes parameter is included in the unattend.txt answer file.

D. Verify that the network interface card in the master computer is plugged in to the crossover cable.

Correct: A B

NO.2 You are a system builder. The company network is not functional, and there is no network

access to the technician computer. You need to preinstall Microsoft Windows? operating systems

on three computers. You have three copies of the Windows operating systems. You have decided

to use a winnt.sif file to perform a Windows CD-based preinstallation on these computers.

You

manually create a winnt.sif file and copy it to three floppy disks. You place a CD of each Windows

operating system in the DVD drive of each computer. You start each computer. When you see the

initialization screen on each computer, you insert the floppy disk with the winnt.sif file on it into

each computer. Two of the computers are preinstalled properly. The third computer, however,

begins the preinstallation process but stops with the command prompt window open and the cursor at D:\i386\System32. You need to preinstall the third computer. What should you do?

(Each

correct answer presents part of the solution. Choose two.)

A.Remove the CD from the drive, clean it, and begin the process again.

B.Check the Hardware Compatibility list to make sure that all hardware is compliant.

C.At the command prompt, type ipconfig /all to make sure that Transmission Control Protocol/Internet

Protocol (TCP/IP) is bound to the adapter.

D.Remove the Microsoft Windows OEM Preinstallation Kit (OPK) CD from the DVD drive and place the

Windows operating system CD into the DVD drive.

Correct:B D

NO.3 You are a system builder. Your network is using a four-port router that is running Dynamic Host

Configuration Protocol (DHCP). Your technician computer runs Microsoft Windows? 2000

Professional and is connected to the four-port router. You have created a configuration set by using OPKTools. When you attempt the preinstallation on a new computer, you find that the hard

drive is not formatted correctly. You open the winbom.ini answer file in the configuration set, and

you see the following: [Disk1.config] Size1 = * PartitionType1 = PRIMARY FileSystem1 = NTFS

QuickFormat1 = YES You need to perform an unattended preinstallation of Microsoft Windows on

three new computers that you are shipping to customers. What should you do? (Each correct answer presents part of the solution. Choose two.)

A.Add Wipe Disk=Yes to the winbom.ini answer file.

B.Add SetActive1=Yes to the winbom.ini answer file.

C.Change Size1=* to Size1=10000 in the winbom.ini answer file.

D.Change QuickFormat1=YES to QuickFormat1=NO in the winbom.ini answer file.

Correct:A B

NO.4 You are a system builder. Your network uses a Microsoft Windows Server? 2003 that is running

the Dynamic Host Configuration Protocol (DHCP) service and is set up as a technician computer.

You installed OPKTools from Microsoft Windows? XP Service Pack 2. You want to set a static

Internet Protocol (IP) address for the Microsoft Windows Preinstallation Environment on the computer that you are installing for your customer. During the preinstallation process, you receive the following error message: Cannot Authenticate to Server. What should you do?

(Each

correct answer presents part of the solution. Choose two.)

A.Edit the winbom.ini file in the WinPE.net section to include the Gateway= parameter.

B.Edit the winbom.ini file in the WinPE.net section to include the StartNet= parameter.

C.Edit the winbom.ini file in the WinPE.net section to include WinPEFirewall=On.

D.Edit the winbom.ini file in the WinPE.net section to include the IPConfig= parameter.

Correct:A D

NO.5 You are a system builder. Your network is using a four-port router that is running the Dynamic

Host Configuration Protocol (DHCP) service. Your technician computer runs Microsoft Windows?

2000 Professional and is connected to the four-port router. You have installed a media reader card

in a computer, and you use OPKTools to preinstall this computer over the network. In Audit mode

you discover that the media card reader device has failed and that it is not enumerated in Device

Manager. You need to preinstall your computers with this card reader. What should you do?

(Each

correct answer presents part of the solution. Choose two.)

A.Add the DriverSigningPolicy=Ignore parameter in the Unattended section of the unattend.txt answer file

to preinstall the unsigned driver.

B.Remove the incorrect driver that was installed.

C.Add the DriverSigningPolicy=Warn parameter in the Unattended section of the unattend.txt answer file.

D.Obtain an updated driver (if one exists) from the manufacturer.

E.Run sigverif.exe from a command prompt to verify that all the drivers are signed.

F.Add the DriverSigningPolicy=Block parameter in the Unattended section of the unattend.txt answer file.

Correct:A D

